

S13 1U, 3 Port Sliding Patch Panel





Description


This innovative, robust 1U sliding patch panel. This panel has been designed to accept up to 3 LGX Modules or MTP/MPO cassettes within a 1U space.

With the ability to use a full array of adaptor types offering a flexible solution to the end user, enabling them to incorporate a multi functional panel which allow easy access during installation or re-work with no disturbance of the existing cable or fibres.

In the addition to the array of adaptors the panel also offers multiple cable entry solutions, up to 6 standard cable entry points for, loose tube, tight buffer, pre terminated and steel tape armoured cable.

Applications

- Data centres, premise installations, telecommunication networks
- Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- Data communication
- Indoor applications



Features/Benefits

- ▶ Up to 3 LGX/MTP modules in 1U
- Multiple Adaptor options available
- Individually labelled ports
- 45° open working angle
- Accepts loose tube, distribution and pre terminated cables
- ROHS, REACH and SvHC
- ► Fits standard 19"

Technical Specification

	_
Element	Characteristic
Height	1U (44.4mm)
Width	483mm
Depth	200mm
Net weight	2.4kg
Packaged weight	2.7kg
Packaged dimensions	530mm (W) x 55mm (H) x 260mm (D)
IP rating	IP20
Suitable for adaptor type	LGX / MTP
Number of ports	3
Cable entry 20mm	6
Mounting adjustment range	50mm
Material	Cold rolled steel
Material thickness	1.2mm
Material coating	Electrostatic powder coating
Colour	Black RAL 9004
Operating temperature	-40°C to +60°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1
Compliant to	RoHS, Reach/SVHC



S13 1U, 3 Port Sliding Patch Panel

