

DETAIL B

3/8" SQUARE MTG HOLES 19"EIA 310-D COMPLIANT

PERFORATED TOP PANEL SHOWN FOR REFERENCE



TOP VIEW

CABLE ACCESS CUT OUT COVERED WITH BRUSH GROMMET



19" 9 RMU

DETAIL C



TOP VIEW

PLEXIGLASS FRONT DOOR SHOWN FOR REFERENCE 180° SWING (TYPICAL FRONT AND REAR)



PAIR OF SOLID LIFT OFF SIDE PANELS w/LOCK AND FINGER RELEASE LATCHES



FRONT VIEW (DOORS REMOVED)

FRONT VIEW

RIGHT SIDE VIEW

SECTION A-A (RIGHT SIDE VIEW)

•PLEXI-GLASS FRONT DOOR, SHOWN FOR REFERENCE
•LIFT OFF AND FIELD REVERSIBLE (FRONT AND REAR)

LEVELING GLIDES M12 THREADED HOLES



CABLE ACCESS AREA

Ø15mm FLOOR MOUNTING HOLE

OPTIONAL CASTER MOUNTING LOCATIONS

BOTTOM VIEW

SPECIFICATIONS:

RACK SPACES: 19" EIA 310-D COMPLIANT - SEE CHART

WEIGHT CAPACITY: 500kg
(BOLTED TO FLOOR, LEVELERS, OR ON CASTERS.)

COLOR: DURABLE TEXTURED BLACK POWDER COATING

CONSTRUCTION: 2 PAIR MOUNTING RAILS, 2.5mm C.R.S.
FULLY WELDED FRAME, 1.5mm C.R.S.
DOORS, SIDE PANELS, TOP PANEL, 1.5mm C.R.S.

HARDWARE: PACKAGE OF QTY-20, M6 SCREWS AND CAGE NUTS, INCLUDED.

W- 600mm WIDE ENCLOSURES				
RMU - TOTAL	H - HEIGHT [mm]	D- DEPTH 600mm	D- DEPTH 800mm	D- DEPTH 1000mm
18	908	o	o	o
24	1219	o	o	o
32	1524	o	o	o
37	1829	o	o	o
42	1981	o	o	o
47	2136	o	o	o

W-750mm WIDE ENCLOSURE				
RMU - TOTAL	H- HEIGHT [mm]	D- DEPTH 600mm	D- DEPTH 800mm	D- DEPTH 1000mm
42	1981	o	o	o
47	2136		o	o

RAIL DEPTH		
DEPTH 600mm	DEPTH 800mm	DEPTH 1000mm
18.25"/ 464mm	18.25"/ 464mm	29"/ 737mm